

20' CONTAINER REEFER NICHE

STAINLESS STEEL/CORTEN STEEL



External	length width height	6.058 mm 2.438 mm 2.591 mm
Internal	length width height	5.035 mm 2.294 mm 2.316 mm
Door opening	width height	2.200 mm 2.266 mm
Max gross weight Payload Tare weight Reefer Machinery		30.480 kg XX.XXX kg 2.850 kg + Machinery
Cubic capacity		26,75 m ³ /944 cu.ft
Fork Pocket	width height centre distance	360 mm 116 mm 2,050 mm
Handling devices	Top and bottom corner castings in ISO 20' position	
Stacking	192.000 kg.	
Floor strength	5.460 kg axle loading	

containertech as

Gramveien 16, 1832 Askim, Norway
 Tel: +476988 7970 - Telefax +47 6988 7979
 www.containertech.no - e-mail: post@containertech.no



Plastic Curtain in door end



Aluminium Floor w/Pallet guides



Internal locking security for Personal door



STANDARDS

Container complies with following standards and their latest editions:
ISO/TC-104

- 668 Series 1 freight containers-Classification, external dimensions and ratings
- 6346 Coding, identification and marking for freight containers
- 1161 Specification of corner fittings for series 1 freight containers
- 1496/1 Specification and testing of series 1 freight containers
Part 1 : General cargo containers for general purposes
- 830 Freight containers-Terminology

The International Union of Railway (UIC) code 592-2 OR.

The Customs Convention on the International Transport of Goods (TIR).

The International Convention for Safe Containers (CSC).

Machinery after customer's specification

containertech as

Gramveien 16, 1832 Askim, Norway

Tel: +476988 7970 - Telefax +47 6988 7979

www.containertech.no - e-mail: post@containertech.no